

A-230 PACKAGE AMPLIFIER



***Ready-to-install package amplifier with simple,
easy-to-use functions and
excellent cost performance.***



A-230 PACKAGE AMPLIFIER

The A-230 is designed to deliver consistently high-quality performance and reliability along with easy installation and simple operation. Separate bass and treble tone control functions make the sound clearer and more pleasing to the listener, while Mic 1 auto-muting facilitates announcements at any time, with a quick return to regular operation.

FEATURES

Cost effective package amplifier that's compact, lightweight and best suited for paging and background music distribution.

- Two microphone inputs, two auxiliary inputs.
- Ultra high performance with wide frequency response.
- Low noise and distortion.
- Separate Bass and Treble controls.
- Attenuation of other input signals from 0 to -30dB by Mic 1 input signal.

SPECIFICATION

Power Source:	240V AC, 50Hz
Rated Output:	30W
Power Consumption:	34W (AC operation at 1/8 rated output, measured on EN60065)
Frequency Response:	50Hz – 20kHz (±3dB)
Distortion:	1% or less at 1kHz, 1/3 rated power
Input:	MIC 1:-60dB* (1.0mV), 600Ω, unbalanced, equivalent to 5-pin DIN type MIC 2:-60dB* (1.0mV), 600Ω, unbalanced, equivalent to phone jack type AUX 1-2:-20dB* (100mV), 10kΩ, unbalanced, RCA pin jack
Output:	Speaker out: Floating balanced High impedance: 330Ω (100V) Low impedance: 4Ω (11V)
S/N Ratio:	60dB or more (MIC 1, 2) 70dB or more (AUX 1, 2)
Tone Control:	Bass: -10dB at 100Hz Treble: -10dB at 10kHz
Muting:	MIC 1 overrides other Mic inputs and AUX inputs with 0 – 30dB attenuation, attenuation by switch
Indicator:	Power LED, Signal LED
Finish:	Panel: ABS resin, black, hair line Case: Steel plate, black
Dimensions:	350 (W) × 105 (H) × 243 (D)mm (13.78" × 3.97" × 9.58")
Weight:	3.5kg (7.72 lb)*0dB = 1V

SYSTEM EXAMPLES

