**AVID3AC:** In-wall Stereo Amplifier 2x 15W,

AC powered

• **AVID3ACBT:** In-wall Stereo Amplifier 2x 15W, AC powered, with Bluetooth

The AVID3 In-wall Amplifier from Clever Little Box is a stylish  $2\times15W$  stereo amplifier for in-wall or dado conduit mounting.

The AVID3ACBT version includes Bluetooth connectivity, providing fast, simple wireless connection of Bluetooth-enabled devices such as smartphones, tablets, iPhones, iPods, etc.

An ideal solution for AV and single-room voice or sound reinforcement applications, the AVID3 Stereo Amplfier is fitted into a 2-gang wallplate and features 2 x audio source inputs (3.5mm jack, screw terminal), line level sensitivity switch and bright LED display.

Supplied as standard, the AVID remote control unit provides ON/OFF, volume, tone and balance control.

The AVID3 compact amplifier is ideal for applications such as classrooms, boardrooms, meeting or demo rooms and domestic home installations.

Both models are 230v AC powered via screw terminals connected on the rear panel.

## Features:

- Stereo amplifier fitted to UK 2-gang Wallplate
- New higher power 2 x 15W output (RMS)
- 230v AC powered
- Bluetooth connectivity for wireless input of iPhone, iPad, smartphones, etc (AVID3ACBT version only)
- 2 x Wired Input Sources; Input 1 via front 3.5mm jack or rear screw terminals. Input 2 via rear screw terminals
- · Line Level Sensitivity Switch
- Control of ON/OFF, volume, and tone source selection via illuminated push buttons located on the front panel
- Infrared remote control of ON/OFF, volume, balance and tone facilities (supplied as standard)
- Clear LED level indicator/setting status display (source select and volume)
- Mono/Stereo output jumper on rear
- Screw terminations on the rear of the unit for loudspeakers, power and wired line output
- Separate loudspeaker balance adjustment to allow system set up (control located on rear of unit)
- System also includes IR remote control, remote wallmount bracket and recessed flushmount backbox for AVID amplifier







## Specifications:

Model:	AVID3AC & AVID3ACBT
Output Power	2 x 15W RMS @ 4Ω
Line Inputs	Input 1 via front 3.5mm jack or rear screw terminals Input 2 via rear screw terminals
Line Outputs	Fixed level (Unbalanced) 1v 47k $\Omega$
Bluetooth	AVID3ACBT ONLY: Wireless Bluetooth Receiver (secure Pairing Code)
Frequency Response	40Hz ~ 20KHz
Input Sensitivity	(Lo)200mv / (Hi)1v
Power Requirements	230v AC
Dimensions	165(W) x 100(H) x 35(D) mm
Weight	0.26kg